

### AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

1. (Currently amended) A wireless communication terminal, comprising:

an operating ~~unit~~, unit;

reception field level detecting means for detecting a threshold field level of the a received radio wave, including a determination of whether a threshold field level has been detected;

a control unit for controlling the ~~terminal~~, terminal;

a storage ~~unit~~, unit;

a plurality of wireless communication units each matching a different communication ~~system~~, system; and

switch-over means for switching over from one to another of the wireless communication units, wherein:

the terminal selects one of the communication systems on ~~the~~ a basis of the reception of the threshold field level of a first communication system that is currently selected and of a field level of another second communication system, and

the terminal issues a notice signal when the second communication system has priority and communication with the second communication system is possible.

2. (Currently amended) The wireless communication terminal, as set forth in Claim 1, wherein:

the terminal initiates execution of detection of the reception of the ~~threshold~~ field level of the second communication system when the reception of the threshold field level of the first communication system that is currently selected has become equal to or below a first threshold.

3. (Previously presented) The wireless communication terminal, as set forth in Claim 2, wherein:

the terminal selects the second communication system when the reception of the threshold field level of the first communication system is equal to or below a second threshold that is lower than the first threshold and communication with the second

communication system is possible.

4. (Original) The wireless communication terminal, as set forth in Claim 2, wherein:  
the terminal selects the second communication system when communication with the  
second communication system is possible.

5-6. (Canceled)

7. (Currently amended) The wireless communication terminal, as set forth in Claim 2  
1, wherein:

the terminal selects the second communication system when the second  
communication system has priority and communication with the second communication  
system is possible.

8. (Currently amended) The wireless communication terminal, as set forth in Claim 6  
1, further comprising:

a display unit and a speaker unit, wherein:

the notice signal is at least either a display on the display unit or a sound emitted by  
the speaker unit.

9. (Previously presented) The wireless communication terminal, as set forth in Claim  
1, wherein:

the terminal executes detection of the reception of the threshold field level of the first  
communication system at prescribed intervals of time.

10. (Previously presented) The wireless communication terminal, as set forth in  
Claim 1, further comprising:

a detection unit for detecting a prescribed operation of the terminal wherein:

when the prescribed operation is done at the terminal, the terminal executes detection  
of the reception of the threshold field level of the second communication system.

11. (Original) The wireless communication terminal, as set forth in Claim 10,

wherein:

the terminal selects the second communication system when communication with the first communication system is impossible and communication with the second communication system is possible.

12. (Original) The wireless communication terminal, as set forth in Claim 11,  
wherein:

the terminal determines possibility or impossibility of communication according to a prescribed threshold.

13. (Original) The wireless communication terminal, as set forth in Claim 10,  
wherein:

the terminal issues a notice signal when the second communication system has priority and communication with the second communication system is possible.

14. (Original) The wireless communication terminal, as set forth in Claim 10,  
wherein:

the terminal selects the second communication system when the second communication system has priority and communication with the second communication system is possible.

15. (Original) The wireless communication terminal, as set forth in Claim 13, further comprising:

a display unit and a speaker unit, wherein:

the notice signal is at least either a display on the display unit or a sound emitted by the speaker unit.

16. (Original) The wireless communication terminal, as set forth in Claim 10,  
wherein:

the terminal is foldable.

17. (Original) The wireless communication terminal, as set forth in Claim 16,

wherein:

the prescribed operation is an operation to unfold the terminal.

18. (Original) The wireless communication terminal, as set forth in Claim 10,  
wherein:

the prescribed operation is an operation on the operating unit.

19. (Original) The wireless communication terminal, as set forth in Claim 10, further  
provided with:

a specific key, wherein:

the prescribed operation is an operation on the specific key.

20. (Currently amended) A control method for a wireless communication terminal  
permitting use of a plurality of communication systems, said method comprising:

initiating detection of a reception field level of a second communication system when  
the reception field level of a first communication system that is currently selected is at or  
below a prescribed threshold, and

selecting either communication system on the basis of the reception field levels of  
said two communication systems, wherein:

the terminal initiates execution of detection of the reception of the field level of the  
second communication system when the reception of the threshold field level of the first  
communication system that is currently selected has become equal to or below a first  
threshold, and

the terminal selects the second communication system when the reception of the  
threshold field level of the first communication system is equal to or below a second  
threshold that is lower than the first threshold and communication with the second  
communication system is possible.

21. (Original) The control method, as set forth in Claim 20, wherein:

a notice signal is issued when the second communication system has priority and  
communication with the second communication system is possible.

22. (Original) The control method, as set forth in Claim 20, wherein:  
the second communication system is selected when the second communication system has priority and communication with the second communication system is possible.

23. (Original) A control method for a wireless communication terminal permitting use of a plurality of communication systems, comprising steps of:  
detecting whether or not a prescribed operation has been done on the terminal,  
detecting, when the prescribed operation has been done, a reception field level of another second communication system than a first communication system that is selected then, and  
selecting either communication system on the basis of the reception field levels of said two communication systems.

24. (Original) The control method, as set forth in Claim 23 wherein:  
the terminal is foldable, and said prescribed operation is an operation to unfold the terminal.

25. (Original) The control method, as set forth in Claim 23 wherein:  
the prescribed operation is an operation on the operating unit of the terminal.

26. (Original) The control method, as set forth in Claim 23 wherein:  
the terminal is provided with a specific key, and said prescribed operation is an operation on the specific key.

27. (Original) The control method, as set forth in Claim 23 wherein:  
a notice signal is issued when the second communication system has priority and communication with the second communication system is possible.

28. (Original) The control method, as set forth in Claim 23 wherein:  
the second communication system is selected when the second communication system has priority and communication with the second communication system is possible.